

CURVED SLAT WOOD WALL PANELS



PRODUCT SPECIFICATIONS

DIMENSIONS	Overall thickness: Varies per profile. Profiles that can have a curved backer: Classic Slat, Fin, Torus, Low Profile Mixed Slat, Palladian & Interval. Veneered backer thickness: 3/4"
PANEL WIDTH	4' (smaller widths available upon request)
PANEL HEIGHT	8' (up to 10' available - price increase applies)
VENEER LAYUP	Plain Sawn, Book Matched (White Oak & Ash), Slip Matched (Walnut)
MINIMUM RADIUS	~16"
FINISH	Available Unfinished or Prefinished - see next page
INSTALLATION	Direct through the veneer face between slats

NOTE: Pricing of all solid wood and veneer products experience fluctuations. Please reach out for current pricing for your specific project



URBAN EVOLUTIONS
materials that drive design

(920) 380-4149
2401 W. College Ave Appleton, WI 54914
urbanevolutions.com

CURVED SLAT WOOD WALL PANELS

PRODUCT DATA

Description: Three-dimensional wall and ceiling panels with solid wood slats and veneer kerfed particle board backer.

Species Options: Select White Oak, Select Walnut, Select Ash & Paint Grade (other species available upon custom request).

Source Options: Domestic Timber (Midwest)

Standard Dimensions: 4'x8' or 4'x10' - All panels start with a flush slat and end with a void for seamless butt joint installation.

Weight: 3-5 lbs per square foot

Core: 3/4" Flexible Particle Board Backer, NAF, TSCA Title VI Compliant.

Finish Options: Matte Clear, Premium Oil & Smoke (custom finishes available upon request).

Add-On Options: Edge trim and inside and outside corner pieces available for an additional charge (see page 3).

Site Conditions: For most installations, we recommend a climatic temperature between 55 to 75 degrees Fahrenheit and 30% to 50% humidity level. Environments that do not meet these criteria will cause wood to experience shrinking and swelling issues that damage the product. We cannot guarantee our product's performance in such environments.

Installation: Installation materials are not included and must be purchased separately.

- Direct through the veneer face between slats. #8 screws recommended and plugged to hide fasteners.

Grain and Allowances: Natural color and grain variation occur across panels. White Oak and Walnut panels may include sapwood up to 10% of total panel. Small, sound pin knots may occur in solid wood slats.

LEED: Urban Evolutions veneer panels may contribute toward satisfying the following credits under LEED® v4.1:

- M&R – Material Ingredients – Declare
- M&R – Sourcing of Raw Materials – Material Reuse (Urban Wood), Wood Products (FSC)
- IEQ – Low-Emitting Materials – VOC Emissions Evaluation

Human Health: Certified Clean Air GOLD (CDPH Compliant), Declare Red List Free

End of Life: Panels can be reused in their entirety. Learn more through our [UE Takeback Reuse Program](#).

For further information, please reach out to the following team members:


- Sustainability Inquiries - emma@urbanevolutions.com
- Specification & Product Inquiries - matt@urbanevolutions.com




CURVED SLAT WOOD WALL PANELS

Dimensions in Plan


Dims will vary per profile - see specs per desired profile
Profiles available on kerfed backer: Classic Slat, Fin, Torus
Low Profile Mixed Slat, Palladian, & Interval




Add-On Options



Solid Wood Edge Trim
(covers raw MDF edges)



Solid Wood Inside Corner
(panels butt into corner piece)



Solid Wood Mitered Outside Corner
(panels butt into corner piece)

