



URBAN
EVOLUTIONS
materials that drive design

2401 W. College Avenue, Appleton, WI 54914
920.380.4149 www.urbanevolutions.com

Character White Oak Engineered Flooring General Specifications

Use: Commercial and Residential flooring installations

Recommended Installation: Glue, Float, Nail, or Staple - See UE Engineered Installation Recommendations for more information.

Engineered Construction:

Wear Layer: Solid White Oak.

Wear Layer Thickness: 2mm

Core: Core 360° High Density Fiberboard

Dimensions:

Thickness: ½"

Width: 5"

Lengths: 2'-8' random

Custom thickness and width available upon request

Profile: Tongue and groove

Species: Plain Sawn Character White Oak

Grain and Allowances:

- Natural color variation will occur across floorboards.
- Character Grade: Allows sound and filled knots, mineral streaks, and quartersawn marks.

Finish:

UV Cured Aluminum Oxide Topcoat

Custom Finishes Available on Request

Resistances: Scratch, Stain, Water, Fade, UV, Warp, Slip

Sustainability Attributes:Sourcing & Ecosystem Health:

- FSC® Certified Wood Available on Request

Human Health:

- No added urea-formaldehyde resins

Climate Health:

- Sourced and manufactured in Wisconsin
- Final assembly in Weston, WI

Circularity:

- Flooring may be refinished at least one time

LEED:

MRc4: Wood Products: FSC® License Code (FSC-C199866)

Warranty: 10 Year Commercial Limited Warranty
Limited Lifetime Residential Warranty

Care & Maintenance: The recommended method for cleaning Urban Evolutions Engineered Flooring is with a damp mop and water. Make sure the moisture content is limited to an amount that will evaporate immediately. See UE Engineered Installation Recommendations for more information.