



Red Oak Engineered Flooring – Wheat General Specifications

Use: Commercial and Residential flooring installations

Recommended Installation: Glue, Float, Nail, or Staple - See UE Engineered Installation Recommendations for more information.

Engineered Construction:

Wear Layer: Solid Red Oak. All wear layers are plain sawn cut.

Wear Layer Thickness: 3mm (can be refinished 2+ times)

Core: Quarter Sawn Pine with PVA bond

Dimensions:

Thickness: 5/8"

Width: 7.5"

Lengths: 2'-8' random

Custom thickness and width available upon request

Profile: Tongue and groove, 4-sided micro bevel

Species: Red Oak - Select & Better Grade

Grain and Allowances:

- Natural color and grain variation will occur across floorboards.

Finish:

Wheat Stain with UV Cured Aluminum Oxide Topcoat

Resistances: Scratch, Stain, Water, Fade, UV, Warp, Slip

Sustainability Attributes:

Sourcing & Ecosystem Health:

- Standard wood sourced from domestic, responsibly harvested trees
- FSC® Certified Wood Available on Request

Human Health:

- No added urea-formaldehyde resins

Climate Health:

- Final assembly in Weston, WI

Circularity:

- Flooring may be refinished at least three times

LEED:

MRc4: Wood Products: FSC® License Code (FSC-C199866)

Warranty: 10 Year Commercial Limited Warranty

Limited Lifetime Residential Warranty

Care & Maintenance: The recommended method for cleaning Urban Evolutions Engineered Flooring is with a damp mop and water. Make sure the moisture content is limited to an amount that will evaporate immediately. See UE Engineered Installation Recommendations for more information.