



URBAN
EVOLUTIONS
materials that drive design

2401 W. College Avenue, Appleton, WI 54914
920.380.4149 www.urbanevolutions.com

Sandstone White Oak Engineered Flooring

General Specifications

Use: Commercial and Residential flooring installations

Recommended Installation: Glue, Float, Nail, or Staple – See UE Engineered Flooring Installation Recommendations for more information.

Engineered Construction:

Wear Layer: Solid White Oak. All wear layers are plain sawn cut

Wear Layer Thickness: 4mm (can be refinished 3+ times)

Core: Quarter Sawn Pine with PVA bond

Dimensions:

Thickness: 5/8"

Width: 7.5"

Lengths: 2'-8' random

Profile: Tongue and groove, 4-sided micro bevel

Species: White Oak

Grain and Allowances:

- Natural color variation will occur across floorboards
- Character Grade: Allows sound and filled knots, mineral streaks, and quartersawn marks

Finish:

Wire Brushed

Sandstone Stain with UV Cured Aluminum Oxide Topcoat

Resistances: Scratch, Stain, Water, Fade, UV, Warp, Slip

Sustainability Attributes:

Sourcing & Ecosystem Health:

- Standard wood sourced from domestic, responsibly harvested trees
- FSC® certified wood available on request

Human Health:

- No added urea-formaldehyde resins

Climate Health:

- Final assembly in Weston, WI

Circularity:

- Flooring may be refinished at least three times

LEED:

- MRc4: Wood Products – FSC® License Code (FSC-C199866)

Warranty: 10 Year Commercial Limited Warranty

Limited Lifetime Residential Warranty

Care & Maintenance: The recommended method for cleaning Urban Evolutions Engineered Flooring is with a damp mop and water. Make sure the moisture content is limited to an amount that will evaporate immediately. See UE Engineered Installation Recommendations for more information.