

LIVE SAWN ENGINEERED WHITE OAK FLOORING



PRODUCT SPECIFICATIONS

WEAR LAYER	4mm (can refinish 3+ times) 6mm (can refinish 4+ times)
THICKNESS	5/8" or 3/4"
WIDTH	5"
LENGTHS	2'-8' Random
PROFILE	Tongue and groove with micro bevel
BLOCK CORE	Quarter Sawn Pine with PVA Bond

NOTE: Pricing of all wood flooring products experience fluctuations. Please reach out for current pricing for your specific project

LIVE SAWN ENGINEERED WHITE OAK FLOORING

PRODUCT DATA

Description: Solid wood lamella on lumber block core for commercial and residential flooring installations

Species: Live Sawn White Oak

Sourcing: Wood may be sourced from the following:

- Urban Wood: Salvaged from cities due to damage, disease, natural decline, or development
- Select Harvest: Habitat restoration projects and responsibly harvested forests
- FSC® Certified: FSC License Code (FSC-C199866)

Grain & Allowances: Natural color variation will occur across floor boards

- Characteristics include sound and filled knots, mineral streaks, quartersawn marks, and insect marks.

Finish: Matte Clear with UV Curved Aluminum Oxide Topcoat

- Resistances: Scratch, Stain, Water, Fade, UV, Warp, Slip

Installation: Glue, Float, Nail, or Staple - See [UE Engineered Flooring Installation Recommendations](#) for more information

Warranty: 10 Year Commercial Limited Warranty

Limited Lifetime Residential Warranty

Care & Maintenance: The recommended method for cleaning UE Live Sawn Engineered Flooring is with a damp mop and water. Make sure the moisture content is limited to an amount that will evaporate immediately. See [UE Engineered Flooring Installation Recommendations](#) for more information.

Sustainability Attributes:

Sourcing & Ecosystem Health:

- Standard wood sourced from salvaged and responsibly harvested timber
- FSC® certified wood available on request

Human Health

- Intertek Certified Clean Air Gold - CDPH v1.2 Compliant
- No added urea-formaldehyde resins

Climate Health

- Sourced and manufactured in Wisconsin
- Final assembly in Weston, WI

Circularity

- Flooring may be refinished at least 3x depending on wear layer thickness

LEED:

IEQc4: VOC Emissions Evaluation: CDPH V1.2 Compliant

MRC4: Wood Products: FSC® License Code (FSC-C199866)

For further information, please reach out to the following team members:

- Sustainability Inquiries - Emma@urbanevolutions.com
- Specification & Product Inquiries - Matt@urbanevolutions.com