

# LIVE SAWN ENGINEERED WIDE PLANK ASH FLOORING



## PRODUCT SPECIFICATIONS

WEAR LAYER	4mm (can refinish 3+ times) 6mm (can refinish 4+ times)
THICKNESS	5/8" or 3/4"
WIDTH	7.5" or 10.5"
LENGTHS	2'-8' Random
PROFILE	Tongue and groove with micro bevel
CORE	Quarter Sawn Pine with PVA Bond

NOTE: Pricing of all wood flooring products experience fluctuations. Please reach out for current pricing for your specific project

# LIVE SAWN ENGINEERED WIDE PLANK ASH FLOORING

---

## PRODUCT DATA

**Description:** Solid wood lamella on lumber block core for commercial and residential flooring installations

**Species:** Live Sawn Ash

**Sourcing:** Wood may be sourced from the following:

- Urban Wood: Salvaged from cities due to damage, disease, natural decline, or development
- Select Harvest: Habitat restoration projects and responsibly harvested forests
- FSC® Certified: FSC License Code (FSC-C199866)

**Grain & Allowances:** Natural color variation of heart and sap will occur across floor boards

- Characteristics include sound and filled knots, mineral streaks, quartersawn marks, and insect marks.

**Finish:** Tinted Ash: custom color with UV Curved Aluminum Oxide Topcoat

- Resistances: Scratch, Stain, Water, Fade, UV, Warp, Slip

**Installation:** Glue, Float, Nail, or Staple - See [UE Engineered Flooring Installation Recommendations](#) for more information

**Warranty:** 10 Year Commercial Limited Warranty  
Limited Lifetime Residential Warranty

**Care & Maintenance:** The recommended method for cleaning UE Live Sawn Engineered Flooring is with a damp mop and water. Make sure the moisture content is limited to an amount that will evaporate immediately. See [UE Engineered Flooring Installation Recommendations](#) for more information.

### Sustainability Attributes:

#### Sourcing & Ecosystem Health:

- Standard wood sourced from salvaged and responsibly harvested timber
- FSC® certified wood available on request

#### Human Health

- Intertek Certified Clean Air Gold - CDPH v1.2 Compliant
- No added urea-formaldehyde resins

#### Climate Health

- Sourced and manufactured in Wisconsin
- Final assembly in Weston, WI

#### Circularity

- Flooring may be refinished at least 3x depending on wear layer thickness

#### LEED:

IEQc4: VOC Emissions Evaluation: CDPH V1.2 Compliant

MRC4: Wood Products: FSC® License Code (FSC-C199866)

For further information, please reach out to the following team members:

- Sustainability Inquiries - [Emma@urbanevolutions.com](mailto:Emma@urbanevolutions.com)
- Specification & Product Inquiries - [Matt@urbanevolutions.com](mailto:Matt@urbanevolutions.com)