

URBAN EVOLUTIONS

LIVE SAWN SELECT HEART ASH VENEER WALL & CEILING PANELS – PRODUCT DATA

Description: Wood veneer wall and ceiling panels on MDF.

Source Options: Sustainably Managed Midwest Forests (Select Harvest), Felled City Trees (Urban Wood), FSC® Certified Available on Request (FSC-C199866)

Dimensions: 4'x8' panels standard

Weight: 2.75 - 3lbs per SF

Core: 11/16" MDF, NAF, TSCA Title VI Compliant, Class A Fire Rated and/or FSC Certified Core available on request (FSC-C199866)

Finish Options: Standard finish is Class A Fire Rated and free of Red List chemicals.

Additional Options: Trim and corner pieces available for an additional charge. Unfinished panels are available upon request.

Site Conditions: For most installations, we recommend a climatic temperature between 55 to 75 degrees Fahrenheit and 30% to 50% humidity level. Environments that do not meet these criteria will cause wood to experience shrinking and swelling issues that damage the product. We cannot guarantee our product's performance in such environments.

Installation: Installation materials are not included and must be purchased separately. For wall installation, we recommend using MF375 Monarch Z-Clips. For ceiling installations, please contact us for specific fasteners.

Grain and Allowances

Color: Each panel is comprised of a custom blend of mostly heartwood and limited sapwood. Natural color variation will occur across panels. Color and grain for Select Heart Ash blend are hand selected for consistency.

Grain: Restricted to cathedral grain pattern

Knots: No restriction on pin knots, up to 3-5 knots per panel

Voids: Less than 1" allowed and filled

Mineral Streaks: Light natural mineral streaks allowed

Checks: Tight checks allowed

LEED: Urban Evolutions veneer panels may contribute toward satisfying the following credits under LEED® v4.1:

M&R – Sourcing of Raw Materials – Material Reuse (Urban Wood)

M&R – Sourcing of Raw Materials – Wood Products (FSC Certified – FSC-C199866)

IEQ – Low-Emitting Materials – Formaldehyde Emissions Evaluation (MDF)

PRODUCT DATA

| | |
|------------------|--|
| PANEL DIMENSIONS | Overall standard thickness is ¾" Standard panels include 1mm veneer layer and 11/16" MDF core |
| PANEL WIDTHS | 2' or 4' standard |
| PANEL HEIGHT | 8' standard Up to 10' available (price increase applies, may be subject to longer lead time) |
| LAYUP | Live Sawn, Random Match, Custom Heartwood & Sapwood Grain Mix |
| MINIMUM | 225sf, small batch quantities are available |
| LEAD TIME | 8-10 weeks |

View sustainability information for each product [here](#). Please reach out to Emma Kiel at emma@urbanevolutions.com for sustainability inquiries and Matt Rasmussen at matt@urbanevolutions.com for technical specifications.